

BARE BONES®

No-Rinse / No Scrub Liquifying Stripper

DESCRIPTION

A 55% active speed stripper that easily cuts through multi-layers of burnished floor finish. This "true" no-rinse stripper does not contain potassium hydroxide or sodium hydroxide yet is the fastest working liquifier on the market. Low foaming, no scrub and no rinse features make this product a must for all professional floor care systems.

PRODUCT FEATURES / BENEFITS

- Low foaming / Can be used through automatic scrubbers
- Contains no potassium or sodium hydroxide / Safe for personnel & flooring
- Requires no rinsing / Saves time by eliminating neutralizing and rinsing
- No scrubbing machine needed / Reduces equipment costs & can be used in hard to get to places
- 55% Active / High use dilution for greater economy

DIRECTIONS FOR USE

For the rapid removal of all floor finishes and waxes from resilient flooring including: vinyl, vinyl asbestos, vinyl composition, asphalt, linoleum, and rubber tiles. Also ideal for finished non-resilients such as: terrazzo, marble, ceramic, quarry tile, ceramic, quarry tile, concrete, and poured epoxy flooring. Although excellent for any type of equipment, greatest savings are realized when using automatic scrubbing equipment.

Dilute BARE BONES® following dilution recommendations below. Dilute using cold or mildly warm water only.

Light/Normal Buildup: 8 oz per gallon of water (1:16) Heavy Buildup (Burnished): 20 oz per gallon of water (1:5) Mop/Wet Vacuum Stripping System: Apply liberally with a

mop to an area small enough so as not to allow the product to

dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above procedure before re-application of recommended NCL Floor Finish.

Floor Machine Stripping System: Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: Asphalt tile, Linoleum, and other sensitive floor surfaces may be damaged by contact with stripping solution. We recommend that a spot test be conducted before general

SPECIFICATIONS

Color	Clear
Odor	Sassafras
pH	11.7 ± 0.3
Flash Point	201°F (94°C) TCC
Upper Cloud Point	> 130°F
Lower Cloud Point	< 33°F
Viscosity (cps)	< 5

Water Solubility	Complete	
Finish Removal	Excellent	
Damage to Resilient Tiles	Minimal	
Density (lbs/gal)	8.1 ± 0.1	
Specific Gravity (g/cc)	0.97 ± 0.01	
Free Rinsing	Yes	
Low Foaming	Yes	
Shelf Life 1 year minimum in original unopened container		

SAFETY INFORMATION

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN OR IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF THE REACH OF CHILDREN

Precautionary statement:

Prevention:

Do not breathe mist or vapor. Use only in well-ventilated areas. Wear protective gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep out of reach of children

Response:

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/ doctor. Wash contaminated clothing before reuse.

Storage:

Store locked up. Store in a well-ventilated place. Keep cool. **Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional safety measures: Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com FOR COMMERCIAL AND INDUSTRIAL USE ONLY.





World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123 1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail:info@nclonline.com