ironwear®

Specifications

Hand Protection

Style #4891-W

ASTM ANSI CUT LEVEL A6

> Cut resistance
A6 - 3815 grams
ANSI/ISEA 105-2016
> Impact Protection - ANSI/ISEA 138-2019 Level 1
> Puncture resistance CE EN-388 4
> Extra wide TPR
> Soft, flexible TPR padding to protect fingers and back of hand from impact
> Impact resistant
> High vis for working visibility in dark areas
> Reinforced between thumb and index finger for longevity
> High Impact TPR for flexibility
> Adjustable cuff
> Padded palm with foam nitrile coating
> Breathable material for employee comfort



Description

> **Application:** Can be used for the construction industy and oil industry where an impact glove is needed.
> **Material:** Blend of PE and other engineered fibers
> **Color:** Gray/White
> **Cuff Style:** Continuous knit with hook and loop closure
> **ANSI Cut Level:** A6
> **CE Standard**
(EN 388-2003): Abrasion Resistance | Blade Cut Resistance | Tear Strength Resistance | Puncture Resistance
4 5 4 4
> **Washing Instructions:** Wash gloves in warm or cold water. Temperature not to exceed 110 ° Fahrenheit using mild laundry detergent. Do not use bleach or solvents. Always air-dry the gloves to maintain proper sizing. DO NOT MACHINE DRY.

Specifications

Size	XSM	SM	MD	LG	XL	2XL	3XL	4XL
Hem Color	Black							
Overall Length	23cm / 8.5"	23.5cm / 9"	24cm / 9.5"	25cm / 10"	26cm / 10.5"	26.5cm / 11"	27cm / 11.5"	28cm / 12"
Palm Width	8.5cm / 3"	9cm / 3.25"	9cm / 3.5"	9.5cm / 3.75"	10cm / 4"	10.5cm / 4.15"	11cm / 4.3"	12cm / 5"

Packaging

Packaging	1 pair per poly bag, 12 pairs per large poly bag, 72 pair per case							
Unit	Pair							
Case Pack	72 pair per case							
Case Weight	22lb / 18kg	23lb / 19.8kg	24lb / 10.8kg	26lb / 11.8kg	26.5lb / 12kg	29lb / 13kg	30lb / 13.6kg	31lb / 14kg
Case Dimensions	12" x 18" x 19" / 30.5cm x 46cm x 79cm							

2020 Seabird Way
Riviera Beach, FL 33404

Toll Free (800) 329-2235

ironwear.com
sales@ironwear.com