7/6/2015

PRODUCT SPECIFICATIONS

FALLTECH®
Fall Protection. Precision Engineered.

Carabiner, Large #8447

Features

- Rugged alloy-steel construction.
- Double-locking gate.
- 2 1/4" gate opening.
- Rated at over 8,000 lbs.
- Meets the requirements of OSHA 1926.502 and ANSI Z359.1-2007/Z359.12-2009



Material Specifications

Connectors:	*Alloy Steel; Min. 5,000 lbs. tensile strength*
Connector Gates:	*Alloy Steel; Min. 3,600 lbs. front and side load*

Performance Specifications

Tensile Strength:	*Min. 8,000 lbs.*
Max. Capacity:	*425 lbs.*

Relevant Standards

OSHA:	*CFR1926.502, CFR1910.66*
ANSI:	*A10.32-2004, Z359.1-2007, Z359.12-2009*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.