model 7501TH

Tempered, Gravity-Fed, Portable Eyewash (Haz Loc)

FEATURES & BENEFITS

CONSTRUCTION

FDA approved high-density green polyethylene tank provides the light and durable construction required in a portable unit.

MOUNTING

J-shaped stainless steel wall bracket makes for a well constructed portable mount for easy removal and re-mount.

FLOW CONTROLS

Pulling down the eyewash arm will begin flushing the 9-gallon (34.1 L) portable tank at .4 gpm (1.5 L) for a full 15 minutes, creating a full patterned flushing of the eyes.

DESIGN

Tank comes complete with a wide-fill opening and threaded cap for quick inspection, cleaning, and filling. Unit also comes equipped with top and side handles making relocation easy.

TEMPERED WATER

Heated, insulated blanket provides ANSI compliant tempered water in operating temperatures to -30° F (-34° C). Unit will stay tempered in non-extreme outdoor conditions (below 100° F (38° C)). Installed over the Haws model 7501.

HAZARDOUS LOCATION

Complies with requirements for hazardous locations Class I, Division 2, Groups B, C, D, Temperature code T4; Class II, Division 2, Groups F, G.

OPTIONS

- ☐ Water Additive: Model 9082, 'sterile' bacteriostatic preservative for use in portable eyewash stations. One 5 oz. (148 ml) bottle will preserve 5 to 20 gallons (18.9 to 75.7 L) of potable water for up to three months. Four bottles per carton.
- ☐ Waste Container: Model 9009 is a twenty-gallon (75.7 L) wastewater container constructed of tough yellow polymer resin. Unit is used to collect water during weekly testing of emergency equipment.

For more information, visit www.hawsco.com or call (888) 640-4297.



SPECIFICATIONS

Model 7501TH is a 9-gallon (34 L), tempered, gravity-fed, hazardous location portable eyewash with a Nema 4 heated, insulated blanket to provide ANSI compliant tempered water in ambient operating temperatures to -30° F (-34° C) . Ideal for remote locations without access to continuous potable water. 120V, 2A, 1 phase electrical requirement. Power cord not provided - power connection must be made according to code using Class I Division 2 compliant equipment. Voltage options available. Model 9082 additive not included - order separately.

APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, when suitable facilities for quick flushing of the eyes needs to be provided and a continuous supply of water is not available. Although the 7501TH may be installed in a wide variety of locations, it is ideal for remote areas where protective measures are still needed. Emergency eyewash equipment shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach. Built with CSA certified components, and compliant to ANSI Z358.1

DISCLAIMER: Continued product improvements make specifications subject to change without notice. Check www.hawsco.com for the latest product information and updates.