NOTRAX®


Justrite Safety Group

531 - SAFETY GRID™

PRODUCT INFORMATION BROCHURE




Justrite Safety Group



For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**




531- SAFETY GRID™ has a welded duckboard design that creates an elevated platform for safety and keeps traffic away from moisture making it the perfect choice for locker rooms, showers and pool areas. The PVC vinyl compound resists chemicals, while providing an anti-slip surface and basic fatigue relief.

Material: PVC

Features and Benefits:

- Duckboard design constructed of resilient vinyl
- Creates an elevated platform keeping traffic away from moisture
- Top of rails features a saw-tooth design for added traction

⚠ **WARNING:** This product can expose you to chemicals including di-2-ethylhexyl phthalate and/or diisononyl phthalate which is known to the State of California to cause cancer, birth defects or reproductive harm. For more information, visit www.P65Warnings.ca.gov



MODEL: 531

APPLICATIONS

- Elevated Runs
- Locker Rooms
- Shower Areas
- Pool Areas

SPECIFICATIONS

Roll Sizes	2'x40', 3'x40', 4'x40'
Thickness	1/2"
Cut Lengths	2', 3', and 4' widths (up to 40' long)
Colors	Black, Black/Yellow, Grey, Blue

Performance:

	Good	Better	Best	Superior
Wear Resistance	■	■		
Anti-fatigue Performance	■			
Slip Resistance	■			



Oil/Grease Resistant · Cleaning · Floor Protection · Cut Lengths · Anti-Fatigue · Anti-Slip · Drainage

TESTING DATA

Test	Test Description	Results
ASTM C-1028-96	Static Coefficient of Friction	Dry: 0.69 Wet: 0.55
-	Compression Deflection	@ 20 lbs/in2: 0.030 @ 40 lbs/in2: 0.035
ASTM D-1004-94a-03	Tear Strength	45.6 lbs
ASTM D-2240	Durometer (Shore A)	90
ASTM D-3884	Abrasion Resistance	@ 500 cycles: 0.18% @ 1000 cycles: 0.23%
ASTM D-2859/CPSC FF-170	Surface Flammability/Carpets and Rugs	Pass
ASTM D-1894-01	Modified Slip Test: Avg. C.O.F. (Coefficient of Friction)	VCT: 0.38 Painted Concrete: 0.40 Vinyl Flooring: 0.52 Epoxy Painted Concrete: 0.37
ASTM D-412	Breaking Load & Elongation	Breaking Load - 100.25 lbs/in2 Elongation - 184.14%
-	Colorfastness to Light	3 - 4, Noticeable to Slight Change

*Testing performed by an independent test laboratory.

NOTRAX®
5655 West 73rd Street
Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF: Justrite Safety Group

Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.