E6 SHOCK ABSORBING LANYARD - SP - TWIN LEG - SNAP & FORM HOOKS - 6' (1.8 M)

Product # **V8104426** | Model # **SA-84022-6**



- SP (Shock Pack) lanyards are comprised of "tear webbing" which is woven in a manner that allows the webbing to tear when it has a load applied to it. This tearing absorbs a significant amount of downward force under load, reducing injury. This tear webbing is folded and shrink-wrapped into a compact 1 x 2 x 6" (2.5 x 5 x 15 cm) pack that is sewn into the lanyard next to the body connector.
- Certified to CSA Z259.11-05 standards
- Made with a superior grade, heavy-duty 1-3/4" (45 mm) or 1" (25 mm) polyester webbing for maximum strength or 1/4" (6 mm) galvanized plastic coated cable, with tear webbing shock absorber
- A tear-away absorber limits the arrest force to a maximum of 1,300 lb (6 kN) for the E6 category
- Worker weight of 200 to 386 lb (90 to 175 kg)

TECHNICAL SPECIFICATIONS

Length/Configuration	6' (1.8 m), double leg, 100% tie off
Hooks	1 snap hook (body), 2 form hooks (anchor)
Max. Arrest Force	1,300 lb (6 kN)