PYRAMEX

Neshoba™ ANSI • CE • CSA •

Frameless design with thin flexible temples // Ultra lightweight spectacle – 16 gm

Black Temples | 10 Variations

	S9710S • • •	Clear
	S9710ST • • •	Clear H2X AF
	S9710STM • •	Clear H2MAX AF
	S9720S • • •	Gray
	S9720ST • • •	Gray H2X AF
	S9720STM • •	Gray H2MAX AF
	S9730S • • •	Amber
	S9760S • •	Infinity Blue
	S9770S • •	Silver Mirror
	S9780S • • •	I/O Mirror



General Specifications

Weight: 16 gm

PD: 64 mm

Bridge: 12.3 mm

Lens base: 9.5 curve

Lens size diagonal: 75.8 mm

Lens size vertical: 43.3 mm

Lens thickness: 1.6 mm

Overall length (lens - tip): 151 mm

Overall width (hinge - hinge): 135 mm

Closest point between temple tips: 78 mm

Closest point between lens: 14.5 mm

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% max. visible light

L2.5: 29% max visible light

Part No.	Lens Marking	Temple Marking
S9710S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9710ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9710STM	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9720S	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9720ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9720STM	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9730S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9760S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9770S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9780S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Materials

Lens: polycarbonate

Temples: polycarbonate

Hinge: polycarbonate

Screw: stainless steel

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact