PYRAMEX



Flex-Lyte™ ANSI • CE • CSA •

RUBBER NOSEPIECE | DIELECTRIC | CO-INJECTED TEMPLES

Soft nosepiece for snug fit // Special dielectric hinge design // Slim co-injected temples channel away sweat // Lightweight spectacle – 22 gm

Black and Gray Frame | 5 Variations

SBG10510D • • •	Clear
SBG10510DTM • • •	Clear **H2MAX** AF
SBG10520D • • •	Gray
SBG10520DTM • • •	Gray **H2MAX** AF
SBG10580D • • •	I/O Mirror

Black and Lime Frame | 5 Variations

SBL10510D • • •	Clear
SBL10510DTM • • •	Clear **H2MAX** AF
SBL10520D • • •	Gray
SBL10520DTM • • •	Gray **H2MAX** AF
SBL10580D • • •	I/O Mirror

WATCH THE VIDEO
Vimeo.com/Pyramex/H2MAX

Flex-Lyte™

General Specifications

Weight: 21.9 gm

PD: 64 mm

Bridge: 14.6 mm

Lens base: 9 curve

Lens size diagonal: 82.3 mm

Lens size vertical: 45.3 mm

Lens thickness: 1.6 mm

Overall length (lens - tip): 160 mm

Overall width (hinge - hinge): 131.5 mm

Closest point between temple tips: 70 mm

Closest point between lens: 9.3 mm

Materials

Lens: polycarbonate

Frame: polycarbonate

Temples: polycarbonate & thermoplastic elastomers (TPE)

Hinge: polycarbonate

Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SBG10510D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10510DTM	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10520D	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10520DTM	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10580D	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBL10510D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBL10510DTM	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBL10520D	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBL10520DTM	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBL10580D	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

W: Welding filter

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices