PYRAMEX
Perform At Your Peak™



Goliath® ANSI CE CSA AUS

CO-INJECTED TEMPLES

POLARIZED OPTION

Co-injected, rubber temples

Part No.	Black Frame
SB5610D ●●●●	Clear
SB5610DT ●●	AF Clear H2X
SB5620D ●●●●	Gray
SB5620DT ●●●●	AF Gray H2X
SB5621D ●●●●	Polarized Gray
SB5645D ●●●	Ice Orange Mirror
SB5665D ●●●●	Ice Blue Mirror
SB5670D ●●●	Silver Mirror
SB5680D ●●	I/O Mirror
Part No.	**White Frame**
SW5620D ●●●●	Gray
SW5655D ●●●	Sky Red Mirror
SW5665D ●●●●	Ice Blue Mirror





There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (•) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (•), Canadian (CSA Z94.3) (•) or Australian (AS/NZS 1337) (•) standards.

PYRAMEX
Perform At Your Peak™

Goliath®

General Specifications

Weight: 35 gm
PD: 68 mm
Bridge: 13.8 mm
Lens base: 8 curve
Lens size diagonal: 62.6 mm
Lens size vertical: 37.6 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 163.5 mm
Overall width (hinge - hinge): 131 mm
Closest point between temple tips: 96.5 mm
Closest point between lens: 18 mm

Materials

Lens: polycarbonate
Temples: polycarbonate & thermoplastic rubbers (TPR)
Hinge: polycarbonate
Screw: stainless steel
Side shields: polycarbonate

Part No.	Lens Markings	Frame Markings
SB5610D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5610DT	P Z87 + U6	P Z87 +
SB5620D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5620DT	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5621D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5645D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5665D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5670D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5680D	P Z87 + U6 L1.7	P Z87 +
SW5620D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SW5655D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SW5665D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
S: Special purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% max visible light
L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967