Sellstrom
ARCFLASH Faceshield
31223 and 31224

Specification & Data Sheet



Part Number	31223 –12 cal/cm² Anti-Fog Window Complete with Hard Hat 31224 –12 cal/cm² Anti-Fog Window with Dielectric Adapter
Description and Performance	Sellstrom's ARCFLASH faceshield provide the best possible clarity with absolutely no distortion. Rugged, polycarbonate shield is high impact and chemical splash resistant and provides excellent color definition. The shield curves naturally to fit facial contours ensuring reliable protection from low level arc flash hazards. Light green tint allows for 55% light transmittance for best clarity. Interchangeable parts extend the life of the face shield and lower cost of ownership. Faceshield available with an adjustable thirty five position ratchet headgear suspension hard hat.
Standards Compliance	Meets ANSI Z87+ High impact, ASTM F2178, NFPA 70E standards
Arc Thermal Protective Value	12 cal/cm²
Materials	
Hard Hat Adapter	Dielectric ABS Plastic and rubber retainers
Window	High impact resistant .060" Molded Polycarbonate, light green tint
Hard Hat	HDPE (see 69500 for complete specifications)
Dimensions	9 3/4" x 20" x .060" viewing area
Weight	.54 lbs (8.64 oz) Faceshield only 1.44 lbs. (23.4 oz)with hard hat
Country of Origin	Made in Taiwan

Sellstrom Manufacturing Company
2050 Hammond Drive, Schaumburg,Illinois 60173
phone 847.358.2000 toll free 800.323.7402 fax 847.358.8564
web www.sellstrom.com | email sellstrom@sellstrom.com

sellstrom®
Product that works.