A560000

Single Sided I-Beam Sliding Anchorage Connector

FEATURES

- Lightweight aluminum design moves smoothly across beam.
- Fits beam flanges from 3 ½ inches to 14 inches.
- Fits beams up to ¼ to 1 ¼ inch thick.
- Minimum Breaking Strength (MBS): 5,000 pounds.
- Meets the requirements of ANSI Z359.18-2017 Type A.



SPECIFICATIONS

Model No.	Material	Connection Size	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A560000	Aluminum	2-1/4 in (57 mm)	5,000 lbs (22.2 kN)	3.3 lbs (1.5 kg)	ANSI Z359.18-2017 Type A OSHA 1910 & 1926

⚠ **WARNING:** Compliant fall protection equipment must only be used as it was designed. Users MUST read and understand all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to follow these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet

WernerCo Corporate Headquarters: 93 Werner Rd., Greenville, PA 16125-9499
TEL: 888-523-3370 FAX: (724) 588-0315 www.wernerco.com

TDSA560000_REVA ©2021 WernerCo 1/21