

# GEMTOR™

... when your life is on the line™

## SPEC SHEET 540PS D-Ring Extension

**Minimum Breaking Strength:**  
5000 lbs.

**Length:**  
18" (bearing point to bearing point)

### Component Specifications: Webbing:

**Material:** Polyester  
**Width:** 1"  
**Color:** Yellow  
**Minimum Breaking Strength:** 9,800 lbs.  
**Melting Point:** 480° F  
**Elongation:** Low to Moderate

### Stitching:

Extra heavy weight bonded polyester thread, sewn with computer controlled lock stitch pattern sewers, all patterns back tacked to prevent unraveling.

### Model Harness Connector:

Model # 5155 Locking Snaphook  
**Minimum Breaking Strength:** 5000 lbs.  
**Gate Strength:** 3600 lbs. (ANSI Z359.12-2012 compliant)  
**Material:** Alloy Steel, zinc plated for corrosion resistance  
**Gate Opening:** 5/8"

### Second End: Full size D-ring

**Minimum Breaking Strength:** 5000 lbs.  
**Material:** Alloy Steel zinc plated for corrosion resistance

### Standard Compliance:

OSHA, ANSI A10.32, ANSI Z359.1

### Available Models:

**540PS** - Snaphook for connection to harness dorsal D-ring

### Special Features & Selling Points:

This extension makes connection and disconnection of lanyard or SRL quicker, safer and easier. No need to reach back D-ring or rely on feel or sound of connection of lanyard or SRL to harness D-ring. Allows harness connection point to be moved outside of outerwear.

