



... when your life is on the line™

# SPEC SHEET A-626L Series Wire Rope Lifelines

**Minimum Breaking Strength:**  
5,000 lbs.

**Capacity:**  
One Worker, 350 lbs.  
Note: This product may be used by workers weighing more than 350 lbs. (including tools and equipment) as long as the system is designed and used in a manner that limits maximum arresting force to less than 1800 lbs.

### Component Specifications:

**Wire Rope:**  
**Material:** Galvanized Steel  
**Diameter:** 5/16"  
**Construction:** 7 x 19  
**Minimum Breaking Strength:** 9,800 lbs.



### Terminations:

**Connector:** Gemtor #5155 ANSI Z359.12 compliant locking snaphook, 3600 lbs. gate strength, MBS: 5000 lbs.  
**Ferrule Material:** Copper  
**Free End:** Aluminum stopper Ferrule  
**Swaging method:** Hydraulic press

### Standard Compliance:

OSHA, ANSI Z359.1, Z359.15, ANSI A10.32  
Note: ANSI Z359 applies to workers within the capacity range of 130 - 310 lbs. Compliance with standard only applies when used by workers within this range.

### Available Models:

Model #	Length
A-626L50	50'
A-626L100	100'
A-626L150	150'
A-626L200	200'
A-626L250	250'

Model #	Length
A-626L300	300'
A-626L350	350'
A-626L400	400'
A-626L450	450'
A-626L500	500'

Custom lengths available

A-626L Spec Sheet Rev. 2/20



Gemtor, Inc. • One Johnson Avenue • Matawan, NJ 07747  
Phone: 732-583-6200 • 800-405-9048 • Fax: 732-290-9391  
Web: www.gemtor.com • Email: sales.info@gemtor.com

