

GEMTOR™

... when your life is on the line™

Spec Sheet AS-2 Series Anchor Sling

Webbing:

Strength Member: 1 3/4" wide 8,800 lb. polyester

Wear Pad: 3" wide 18,000 lb. polyester

Hardware:

Zinc plated alloy steel D-rings

Stitching:

High tenacity 6 cord polyester thread

Minimum Breaking Strength:

5000 lbs.

Colors:

Strength Member: Blue

Wear Pad: Yellow

Other Features:

This is a choker style Anchor sling that has one larger and one standard size, snaphook compatible D-ring, connection is made to the standard size D-ring.

Available Models:

Model #	Material	Length
AS-2-3	Polyester	3'
AS-2-4	Polyester	4'
AS-2-6	Polyester	6'
AS-2-#*	Polyester	Specify

*Sling can be ordered in virtually any length, replace # with required length

Standard Compliance:

OSHA, ANSI A10.32, ANSI Z359.1-2007

Special Features & Selling Points:

Heavy-duty wear pad, can be wrapped around virtually any structural support capable of supporting at least 5000 lbs. provides extremely versatile connection to wide variety of anchorages, The AS-2 is a choker style anchor that remains in place and can also be used to attach horizontal lifeline systems to vertical columns economical, standards compliance.

Similar Models:

AS-1 Series is made of the same materials and construction as the AS-2 Series but has two like size D-rings and connection is made to both D-rings. AS-1 can be used on closed end horizontal beams, etc. and allows the sling to be "slid" along as a moveable anchorage.



Rev. 10/11



Gemtor, Inc. • One Johnson Avenue • Matawan, NJ 07747
Phone: 732-583-6200 • 800-405-9048 • Fax: 732-290-9391
Web: www.gemtor.com • Email: sales.info@gemtor.com

