

## SPEC SHEET

### SELF-RETRACTING LIFELINES

#### Housing:

**SRL series:** plated and painted stamped steel

**SL2 series:** painted cast aluminum

**SWL-11:** painted cast aluminum

**SWL-20 & 30:** plated and painted stamped steel

#### Lifeline:

**SRL and SL2 series:** 3/16" diameter galvanized or stainless steel wire rope. 3/16" diameter Spectra non-conductive, synthetic rope also available.

**SWL series:** 1" wide polyester web

#### Internal Components:

Bronze, stainless steel and aluminum

#### Connector at end of lifeline:

Model # 3154 swivel, locking snaphook

#### Impact Indicator:

**SRL & SL2 series:** located at end of lifeline just above snaphook

**SWL series:** located on housing



#### Available Models:

Model #	Lifeline Type	Lifeline Material	Lifeline Length	Housing	Weight
SRL-30	Wire Rope	Galvanized Steel	30 ft.	Steel	20 lbs.
SRL-30S	Wire Rope	Stainless Steel	30 ft.	Steel	20 lbs.
SRL-50	Wire Rope	Galvanized Steel	50 ft.	Steel	27 lbs.
SRL-50S	Wire Rope	Stainless Steel	50 ft.	Steel	27 lbs.
SRL-65	Wire Rope	Galvanized Steel	65 ft.	Steel	30 lbs.
SRL-65S	Wire Rope	Stainless Steel	65 ft.	Steel	30 lbs.
SL2-30	Wire Rope	Galvanized Steel	30 ft.	Aluminum	20 lbs.
SL2-30S	Wire Rope	Stainless Steel	30 ft.	Aluminum	20 lbs.
SL2-50	Wire Rope	Galvanized Steel	50 ft.	Aluminum	29 lbs.
SL2-50S	Wire Rope	Stainless Steel	50 ft.	Aluminum	29 lbs.
SL2-100	Wire Rope	Galvanized Steel	100 ft.	Aluminum	45 lbs.
SL2-100S	Wire Rope	Stainless Steel	100 ft.	Aluminum	45 lbs.
SWL-11	Web	Polyester	11 ft.	Aluminum	8.25 lbs.
SWL-20	Web	Polyester	20 ft.	Steel	13.5 lbs.
SWL-30	Web	Polyester	30 ft.	Steel	14.5 lbs.

#### Standard Compliance:

OSHA, ANSI A10.14, ANSI Z359.1, CSA Z259.1 (available on SRL & SL2)

#### Special Features & Selling Points:

**All Models** – Automatically extend and retract permitting a worker freedom of movement while preventing slack line and providing continuous protection against falls, Weather sealed, sealed ball bearings for smooth extension and retraction of lifeline, Models available to fit virtually any application.