

# GEMTOR™

... when your life is on the line™

## Spec Sheet

### SP11LYDA6 - Soft-Pack Energy Absorbing Lanyard with 18" D-Ring Extension

#### Energy Absorber Pack Webbing:

1 3/4" wide 6000 lb. fade resistant Polyester  
1 3/4" wide special formulated tear webbing

#### Lanyard:

1" wide 9000 lbs. polyester web

#### D-Ring Extension:

1" wide 9000 lbs. polyester web

#### Length:

Adjustable from 4 ft. – 6 ft.

#### Snaphooks:

Model # 5155, zinc plated alloy steel locking snaphook with 3/4" gate opening, 3600 lb. gate strength, meets ANSI Z359.12

#### D-Ring:

Zinc plated forged alloy steel, MBS: 5000 lbs.

#### Soft-Pack Color:

Red

#### Lanyard/Extension Color:

Yellow

#### Standard Compliance:

OSHA, ANSI Z359.1, Z359.13, A10.32, CSA Z259.11

#### Specifications (when tested in accordance with ANSI Z359.13):

- **Max Arresting Force** - less than 900 lbs. (4kN)
- **Average Arresting force** - Less than 900 lbs.
- **Maximum Elongation** - 42" (1.07m)

#### Special Features & Selling Points:

D-ring extensions provides for an easily accessible secondary connection ideal for connecting to an SRD/SRL, Reduces fall arrest forces to less than 900 lbs., clear protective covering for easy visual inspection, high visibility, durable, economical, easy to use, adjustable length.



Rev. 10/21



Gemtor, Inc. • One Johnson Avenue • Matawan, NJ 07747  
Phone: 732-583-6200 • 800-405-9048 • Fax: 732-290-9391  
Web: [www.gemtor.com](http://www.gemtor.com) • Email: [sales.info@gemtor.com](mailto:sales.info@gemtor.com)

