

GEMTOR™

... when your life is on the line™
Since 1985



SRD-30G Self-Retracting Lifeline

Specifications:

Connector: ANSI Z359.12 compliant, zinc plated locking steel snaphook with 3600 lbs. gate strength and impact indicator.

Anchorage Connector: Zinc plated alloy steel, ANSI Z359.12 carabiner with 3600 lbs. gate strength.

Housing: Engineered plastic

Lifeline Material: 30' x 3/16" diameter, 7 x 19, galvanized steel cable.

Standards Compliance: OSHA, ANSI Z359.14-2014 Class A, ANSI A10.32-2012

Weight: 12.6 lbs.

Max Arresting Distance: <24"

Average Arresting Force: <1350 lbs.

Capacity: 310* lbs. (one worker)

*The SRD is designed for use by persons with a combined weight (clothing, tools, etc.) ranging from 130 lbs. (59kg) to 310 lbs. (140kg). Make sure all the components in your system are rated to an appropriate capacity for the application. NOTE: 130-310 lbs. (59-140kg.) is the capacity range allowed by ANSI Z359.14. This SRD has been designed and tested to a capacity of 350 lbs. (159kg) For weights between 310-350 lbs. (140-159kg) use Max. Arrest Distance $\leq 54"$ (1,372mm) to calculate potential fall distances.

Available Models:

SRD-30G - Self-Retracting Device with 30' of galvanized steel cable and swivel locking snaphook w/load Indicator.



SRD_30G_Rev.1-2018



Gemtor, Inc. • One Johnson Avenue • Matawan, NJ 07747
Phone: 732-583-6200 • 800-405-9048 • Fax: 732-290-9391
Web: www.gemtor.com • Email: sales.info@gemtor.com

