

GEMTOR™

... when your life is on the line™
Since 1985



Spec Sheet



Dual Leg 6 ft. Webbing Fall Limiter

Specifications:

Connectors

SRD-T6W - Two (2) ANSI Z359.12 compliant, zinc plated locking steel swivel snaphook with 3/4", 3600 lbs. gate.

SRD-T6WZ - Two (2) ANSI Z359.12 compliant, zinc plated locking rebar snaphook with 2 1/2", 3600 lbs. gate.

Harness Connector: SHC-2, Zinc plated alloy steel, with 3600 lbs. gate strength, Meets ANSI Z359.12

Housing: Engineered Nylon over steel frame

Lifeline Material: 75" wide Ultra-high-molecular-weight polyethylene (UHMWPE)/polyester blend webbing, 4000 lbs. MBS

Lifeline Length: 2 x 6 ft.

Weight: 4.2 - 5.75 lbs.

Max Arresting Distance: <24"

Average Arresting Force: <1350 lbs.

Capacity: 310*lbs. (one worker)

*NOTE: 130-310 lbs. (59-140kg.) is the capacity range allowed by ANSI Z359.14. This SRD has been designed and tested to a capacity of 350 lbs. (159kg)

Standards Compliance: OSHA, ANSI Z359.14-2014 Class A, ANSI A10-32-2012

SRD-T6W_Rev_1-2018