

Product Specifications

Item #ADS189STPR, ADS229STPR



M-GARD®

Magid® M-GARD® AeroDex® ADS 13-Gauge Extremely Lightweight Cut Resistant Sleeve with Thumb Slot – Cut Level A9

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Sleeves - Cut Resistant
Construction/Design	Single-ply, tubular knit, 1.5" hook and loop closure with gusset at bicep, thumb slot
Composition	AeroDex® yarn
Color(s)	Blue sleeve, black cuff and hook & loop closure at bicep
Size(s)	18", 22" lengths available
Cuff/Finish	Thin fiber knit palm and thumb slot with color-coded sewn overedge: Orange (18") Light Blue (22")
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 120 pairs per case
FEATURES & BENEFITS	
• AeroDex® engineered yarn delivers extremely lightweight A9 cut resistance that is 50% lighter than a traditional HPPE of the same cut level • 13-gauge AeroDex is specially engineered to feel cooler than a comparable cut resistant sleeve • Premium 1.5" hook and loop closure with gusset bicep treatment fits all arms • Available in 18" and 22" lengths with a thumb slot • Thumb slot with thin fiber knit palm keeps the sleeve from riding up and reduces bulk when wearing gloves • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Machine washable for longer service life • Separate "left arm" and "right arm" labeled versions for enhanced comfort and easy identification • ANSI Level A9 Cut Resistance	
APPLICATIONS	
Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling, Maintenance, Assembly	

AVAILABLE STYLES		
Size	18"	22"
Item Number	ADS189STPR	ADS229STPR
FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	A9
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
It is recommended that the sleeves be machine washed. The water temperature cannot exceed 40°C/104°F. Do not use bleach. The sleeves can be air dried or tumbled dry on low temperature.		

Originator	Scott Daigle	Date	9/21/2022	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.