

# Product Specifications

Item #GP148



## ROC<sup>®</sup>

Magid<sup>®</sup> ROC<sup>®</sup> GP148 Lightweight TriTek Palm<sup>®</sup>  
Coated General Purpose Work Glove

PRODUCT DESCRIPTION	
Product Classification	General Purpose Work Glove – Coated
Construction/Design	15-gauge, seamless machine knit
Composition	Nylon/Spandex blend shell; TriTek Palm <sup>®</sup> coating
Color(s)	Navy blue shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Dozen (minimum order: 12 dozen)
Packaging	12 dozen pairs per inner pack, 144 dozen per case

FEATURES & BENEFITS	
<ul style="list-style-type: none"><li>• 15-gauge nylon and spandex shell is form-fitting and breathable for a bare-hands feel</li><li>• Flexible dual-layer TriTek Palm<sup>®</sup> coating strengthens grip and minimizes saturation in heavy liquid and oil applications</li><li>• Resilient TriTek Palm<sup>®</sup> coating provides over 2X the abrasion resistance of other coatings for unbeatable durability while maintaining extreme dexterity</li><li>• Color-coded overcast acts as a visual aid for sizing and reduces fraying</li><li>• Machine washable for longer service life</li><li>• ANSI Level A1 Cut Resistance, ANSI Level 4 Abrasion Resistance</li></ul>	

APPLICATIONS	
Shipping and receiving, assembly, material handling, and general maintenance	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GP1485	GP1486	GP1487	GP1488	GP1489	GP14810	GP14811	GP14812

## FUNCTIONAL PERFORMANCE

### US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A1
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4

## SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

<b>Critical Defects</b>	Holes/tears
<b>Major Defects</b>	Dimensional or weight nonconformance, discoloration, other fabric defects

## LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

<b>Originator</b>	Scott Daigle	<b>Date</b>	12/9/2019		
<b>Revised By</b>	Kim Schultz	<b>Date</b>	4/25/2024	<b>Revision #</b>	4

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD