

Product Specifications

Style #GPD267



D-ROC®
by Magid

Touchscreen Compatible Polyurethane Palm Coated Work Gloves – Cut Level A3

For jobs that involve handling sharp materials, the GPD267 Hyperon™ work gloves deliver 360° ANSI Level A3 cut protection, cool comfort, and touchscreen compatibility.

PRODUCT DESCRIPTION								
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated							
Construction/Design	15-gauge, seamless machine knit, touchscreen compatible							
Composition	Hyperon™ shell; polyurethane palm coating							
Color(s)	Blue shell; grey palm coating							
Size(s)	5 – 12							
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), white (11), orange (12)							
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)							
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)							
FEATURES & BENEFITS								
• Form-fitting 15-gauge Hyperon™ shell delivers dexterity and cool comfort plus 360° cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Touchscreen compatible in all fingers • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A3 Cut Resistance, ANSI Level 5 Abrasion Resistance, and ANSI Level 3 Puncture Resistance								
APPLICATIONS								
Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.								
AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD2675	GPD2676	GPD2677	GPD2678	GPD2679	GPD26710	GPD26711	GPD26712
FUNCTIONAL PERFORMANCE								

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A3
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	5
EN 388:2003 Puncture Resistance	6.4	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	9/20/2017	
Revised By	Kim Schultz	Date	2/15/2024	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.