

Product Specifications

Item #GPD416



D-ROC® 21G

Magid® D-ROC® GPD416 21G Ultra-Thin
Foam Nitrile Palm Coated Work Gloves – ANSI Cut Level A4

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	21-gauge, seamless machine knit shell
Composition	21G fiber blend shell; foam nitrile palm coating
Color(s)	Black
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• Ultra-thin 21-gauge knit construction delivers revolutionary bare-hand dexterity and tactile sensitivity • Specially engineered 21G lightweight fiber technology provides extreme comfort and A4 cut resistance • Foam nitrile palm coating channels oil away for superb grip in light oil applications • Touchscreen compatible work gloves maintain user safety while operating electronic devices • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Nitrile reinforced thumb saddle enhances durability at a critical wear point • Color-coded overcast acts as a visual aid for sizing and reduced fraying • Machine washable for longer service life • ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Level 3 Puncture Resistance	

APPLICATIONS	
Material handling, electrical contractors, assembly line, mechanics repair, maintenance and shipping & receiving. Especially relevant for jobs that require handling of small parts and hand dexterity.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD4165	GPD4166	GPD4167	GPD4168	GPD4169	GPD41610	GPD41611	GPD41612

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A4
ASTM D338-10 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
EN 388 Puncture Resistance	6.4	3

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Kim Schultz	Date	01/19/2024	
Revised By	Kim Schultz	Date	05/15/2024	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.