

Product Specifications

Style #GPD487



D-ROC®
by Magid

D-ROC® GPD487 Hyperon® 13-Gauge RepTek Grip® Silicone Palm Coated Work Glove – Cut Level A5

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; RepTek Grip® silicone palm
Color(s)	Salt & pepper shell; clear palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 144 pairs per case
FEATURES & BENEFITS	
• 13-gauge Hyperon® shell is cool and lightweight for incredible comfort and cut protection • RepTek Grip® silicone palm coating delivers unmatched dry grip and increases heat-resistance • Silicone coating provides adhesion resistance to prevent sealant and hot melt build up • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • H.B. Fuller and PPG Tested • ANSI Level A5 Cut Resistance, ANSI Level 6 Abrasion Resistance, ANSI Level 3 Puncture Resistance	
APPLICATIONS	
Window and door fabrication, hot melt and sealant work, appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD4875	GPD4876	GPD4877	GPD4878	GPD4879	GPD48710	GPD48711	GPD48712

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	6
EN 388:2003 Puncture Resistance	6.4	3

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	3/10/2020	
Revised By	Kim Schultz	Date	06/23/2026	Revision # 5

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.