

Product Specifications

Style #GPD651RT



**Magid® Griffin Gear™ GPD651 Hyperon®
Polyurethane Palm Coated Work Gloves with
Reinforced Thumb Saddle– Cut Level A6**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit; reinforced thumb saddle
Composition	Hyperon® and steel blended shell; polyurethane palm coating
Color(s)	Dark grey shell; black palm coating
Size(s)	6 – 11
Cuff/Finish	Color-coded elasticized overcast: grey (6), blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• 13 gauge Hyperon® and steel blended shell delivers breathability, comfort, and 360° cut protection • Polyurethane palm coating delivers optimal dexterity and an excellent grip • Reinforced thumb saddle coating delivers up to 40 times the abrasion resistance at critical wear point • Dark grey color hides dirt and grime to extend wear • Affordable protection to meet the needs of any safety program • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Machine washable for longer service life • ANSI Level A6 Cut Resistance, ANSI Level 5 Abrasion Resistance, and ANSI Level 4 Puncture Resistance	

APPLICATIONS	
Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.	

AVAILABLE STYLES						
Size	6	7	8	9	10	11
Part Number	GPD651RT6	GPD651RT7	GPD651RT8	GPD651RT9	GPD651RT10	GPD651RT11

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A6
ASTM D3389-10 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	5
EN 388:2003 Puncture Resistance	6.4	4
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Scott Daigle	Date	9/8/2022	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.