



# Gym Finish Water-Based Wood Coating

Acrylic water-based floor coating provides long-lasting beauty and protection to all wood floors

## Features & Benefits

- Offers durability and appearance equal or greater than oil-modified products
- Superior traction.
- Excellent black mark, scuff and soil resistance.
- Easily applied with an applicator
- Use on all sealed wood floors

## Usage Instructions

### READ ALL DIRECTIONS BEFORE APPLYING

#### Prepare Floor

- This coating is not designed for application to bare wood floors
- Use only on previously sealed surfaces and after proper procedural training

#### Scrub and recoat

1. Dust mop floor and remove all chewing gum, labels and tape
2. Prepare floor with Swish Prep™ following product label directions NOTE: Test previously coated floor in an inconspicuous area before recoating to determine compatibility with existing coating
3. Apply no more than 2 coats in 24 hours and a maximum of 3 coats in 48 hours
4. See coating application instructions below

#### Apply Coating

1. Apply at a rate of 800-1000 square feet per gallon
2. Use a weighted T-bar with a clean, synthetic pad
3. Apply thin, even coats with the grain of the wood while walking at a slow, even pace. Walking too fast may produce excessive bubbling in the coating
4. Allow a dry time of at least 1-2 hours between coats. Humid conditions require longer dry time
5. After the first coat has dried, apply a second coat. It may be necessary to screen the first coat if grain raising has occurred or it has dried longer than 8 hours. If so, screen the floor with a previously used 100 grit screen or black pad
6. Always vacuum and tack thoroughly after screening



**Caution**

- May cause skin irritation
- May cause serious eye irritation
- May cause respiratory irritation or may cause drowsiness or dizziness
- Dispose of contents/container in accordance with local regulation

**Product Code & Size**

#9002-4      3.78 L x 4 /case

#9002-20    18.9L