

Safety Data Sheet



Division of Fresno Oxygen



Barnes Welding Supply/Barnes Specialty Gases

Division of Fresno Oxygen

2825 S. Elm Ave. #101
Fresno, California 93706
Toll Free: (800) 404-9353
Fax: (559) 233-4206
http://www.barnesweldingsupply.com
E-mail: info@barneswelding.com

Document #: G-104

Emergency Phone:
International

Infotrac 1(800) 535-5053
Infotrac 1(352) 323-3500

Section 1: Product and Company Identification

Barnes Welding Supply / Barnes Specialty Gases - Division of Fresno Oxygen
2825 S. Elm Ave. #101
Fresno, CA 93706
(800) 404-9353 Toll Free
(559) 233-4206 Fax
http://barnesweldingsupply.com
info@barneswelding.com
FOR CHEMICAL EMERGENCIES DURING TRANSPORTATION ONLY CALL INFOTRAC
1-800-535-5053

Product Name: Argon, Refrigerated Liquid

Section 2: Hazards Identification



Warning

Hazard Classification:
Gases Under Pressure

Hazard Statements:
Contains gas under pressure; may explode if heated

Precautionary Statements

Storage:
Protect from sunlight.
Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

CAS #
7440-37-1

Chemical Substance	Chemical Family	Trade Names
ARGON, LIQUID	non-metallic	ARGON; AR; Argon (cryogenic liquid)

Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Warm skin with warm water not to exceed 105°F (41°C).	Flush eyes with plenty of water.	Not applicable route of exposure	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Non-flammable gas	Not applicable	N/A N/A

Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	None known.	Stop leak if possible without personal risk.

Methods for Cleanup	Other Information
Leaks may be detected by a soapy-water solution.	

Section 7: Handling and Storage

Handling	Storage
Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Avoid using in confined spaces.

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines
ACGIH (simple asphyxiant)

Engineering Controls
Handle only in fully enclosed systems.

Eye Protection	Skin Protection	Respiratory Protection
Splash resistant goggles.	Wear insulated clothing.	N/A

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Liquid	Colorless	Colorless	N/A	Liquid	Odorless	Tasteless

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Not flammable			Nonflammable	Nonflammable	Nonflammable

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
-303 F (-186 C)	-308 F (-189 C)	500 mmHg @ -190 C	1.38 (Air=1)	Not applicable	3.36% @ 20 C	Not applicable	Not available	Not applicable	0.0225 cP @ 25 C

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
39.948	AR	1.784 g/L @ 0 C	Not available	100%	Not applicable	Soluble: Organic solvents

Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	No data available.

Hazardous Decomposition Products	Possibility of Hazardous Reactions
No data available.	Will not polymerize.

Section 11: Toxicology Information

Acute Effects

Oral LD50	Dermal LD50	Inhalation
Not established	Not established	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, dizziness, disorientation, mood swings, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma

Eye Irritation	Skin Irritation	Sensitization
Frostbite	Frostbite	ASPHYXIAN, difficulty breathing

Chronic Effects

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not established	Not established	Not established	No data

Section 12: Ecological Information

Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Argon, Liquid	UN1951	2.2	Not applicable	Nonflammable gas	75 kg or L	150 kg	N/A

Canadian Transportation of Dangerous Goods

Shipping Name	UN Number	Class	Packing Group / Risk Group
Argon, liquid	UN1951	2.2	Not applicable

Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
Not regulated.	Not regulated.	Not regulated.

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	No	No	Yes

SARA 372.65

Not regulated.

OSHA Process Safety

Not regulated.

State Regulations

CA Proposition 65

Not regulated.

Canadian Regulations

WHMIS Classification

A

National Inventory Status

US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Listed on inventory.	Not listed.	Listed on inventory.

Section 16: Other Information

NFPA Rating

HEALTH=3 FIRE=0 REACTIVITY=0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard