

Safety Data Sheet



Division of Fresno Oxygen

Barnes Welding Supply/Barnes Specialty Gases

Division of Fresno Oxygen

2825 S. Elm Ave. #101
Fresno, California 93706
Toll Free: (800) 404-9353
Fax: (559) 233-4206
http://www.barnesweldingsupply.com
E-mail: info@barneswelding.com

Document #: G-231

Emergency Phone:
International

Infotrac 1(800) 535-5053
Infotrac 1(352) 323-3500

Section 1: Product and Company Identification

Barnes Welding Supply / Barnes Specialty Gases - Division of Fresno Oxygen

2825 S. Elm Ave. #101
Fresno, CA 93706
(800) 404-9353 Toll Free
(559) 233-4206 Fax
http://barnesweldingsupply.com
info@barneswelding.com
FOR CHEMICAL EMERGENCIES DURING TRANSPORTATION ONLY CALL INFOTRAC 1-800-535-5053

Product Name: 1-Butene
Part Number: 1-Butene

Section 2: Hazards Identification



Danger

Hazard Classification:

Flammable (Category 1)
Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated
Extremely flammable gas

Precautionary Statements

Prevention:
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Response:

Eliminate all ignition sources if safe to do so.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Storage:

Protect from sunlight.
Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

CAS #
106-98-9

Chemical Substance	Chemical Family	Trade Names
1-BUTENE	Hydrocarbons, Aliphatic, Unsaturated	ALPHA-BUTYLENE; ETHYLETHYLENE; BUTYLENE; ALPHA-BUTENE; BUTENE-1; N-BUTENE; N-BUTYLENE; 1-BUTYLENE; UN 1012; C4H8;

Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
If it is safe to do so, remove victim to an uncontaminated area, and place them in a comfortable position to wait for medical attention. Immediately remove contaminated clothes and shoes. Cleanse the affected skin areas thoroughly with soap under running water for 15 minutes. Seek medical treatment.	Rinse the affected eye thoroughly for 10 minutes under running water. Seek immediate medical treatment. For exposure to liquid, immediately warm frostbite area with warm water less than 105F (41C).	Swallowing is not a likely route of exposure.	If it is safe to do so, remove victim to fresh air, and place them in a comfortable position to wait for medical attention. Administer oxygen or artificial respiration if breathing is difficult. Seek immediate medical treatment.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Carbon dioxide, regular dry chemical Large fires: Flood with fine water spray.	Carbon monoxide, carbon dioxide, water and toxic and irritating fumes	- Respiratory protection may be needed for frequent or heavy exposure. - Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard area and deny entry. Do not touch spilled material.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition. Ventilate closed spaces before entering.
Methods for Cleanup	Other Information	
Stop leak, evacuate area and ventilate. Prevent waste from contaminating environment.	N/A	

Section 7: Handling and Storage

Handling	Storage
Keep container tightly closed in a locked area. Protect from sunlight. Protect from ignition sources. Secure cylinders upright to keep them from falling or being knocked over. Store only where temperature will not exceed 125F (52C).	Always handle in a well ventilated area. Use only in closed systems. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. Avoid contact with skin and eyes. Keep away from heat and ignition sources.

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines
1-BUTENE: No occupational exposure limits established.

Engineering Controls

Handle only in fully enclosed systems.

Eye Protection	Skin Protection	Respiratory Protection
Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and shower in work area.	Wear appropriate chemical resistant clothing.	Respiratory protection may be needed for frequent or heavy exposure.

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Gas	Colorless	Colorless	N/A	Gas	Distinct odor	N/A

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
-112 F (-80 C)			725 F (385 C)	0.1	0.016

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
21 F (-6 C)	-301 F (-185 C)	1976 mmHg @ 21.1 C	2 (Air=1)	Not applicable	Insoluble	Not applicable	24 ppm (55 mg/m3) (unspecified)	Not applicable	0.00763 cP @ 20 C

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
56.11	C-H3-C-H2-C-H-C-H2	2.3655 kg/m3 @ 25 C	Not available	100%	Not applicable	Soluble: Alcohol, ether, benzene

Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Metal salts, oxidizing materials, halogens, acids

Hazardous Decomposition Products	Possibility of Hazardous Reactions
Oxides of carbon	Polymerizes with evolution of heat. Avoid contact with incompatible materials.

Section 11: Toxicology Information

Acute Effects

Oral LD50	Dermal LD50	Inhalation
Inhalation LC50 Rat 658 mg/L 4 h	Not established	Mild irritation, nausea, vomiting, symptoms of drunkenness, suffocation, convulsions, coma

Eye Irritation	Skin Irritation	Sensitization
Mild irritation, frostbite, blurred vision	Blisters, frostbite	Central nervous system depression, difficulty breathing

Chronic Effects

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not listed	Not established	Not established	No data

Section 12: Ecological Information

Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Butylene	UN1012	2.1	Not available	2.1	Forbidden	150 kg	N/A

Canadian Transportation of Dangerous Goods

Shipping Name	UN Number	Class	Packing Group / Risk Group
Butylene	UN1012	2.1	N/A

Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
Not regulated.	Not regulated.	Not regulated.

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	Yes	No	Yes

SARA 372.65

Not regulated.

OSHA Process Safety

Not regulated.

State Regulations

CA Proposition 65
Not regulated.

Canadian Regulations

WHMIS Classification
A, B1

National Inventory Status

US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Listed on inventory.	Not listed.	Listed on inventory.

Section 16: Other Information

NFPA Rating
HEALTH=1 FIRE=4 REACTIVITY=0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard