

Safety Data Sheet



Division of Fresno Oxygen

Barnes Welding Supply/Barnes Specialty Gases

Division of Fresno Oxygen

2825 S. Elm Ave. #101
Fresno, California 93706
Toll Free: (800) 404-9353
Fax: (559) 233-4206
http://www.barnesweldingsupply.com
E-mail: info@barneswelding.com

Document #: G-319

Emergency Phone:
International

Infotrac 1(800) 535-5053
Infotrac 1(352) 323-3500

Section 1: Product and Company Identification

Barnes Welding Supply / Barnes Specialty Gases - Division of Fresno Oxygen

2825 S. Elm Ave. #101
Fresno, CA 93706
(800) 404-9353 Toll Free
(559) 233-4206 Fax
http://barnesweldingsupply.com
info@barneswelding.com
FOR CHEMICAL EMERGENCIES DURING TRANSPORTATION ONLY CALL INFOTRAC 1-800-535-5053

Product Name: ET-ME-NB-NP-NH-PR in NI Non-Flammable
Part Number: CS 3500R07F
Synonyms: Non-Flammable Gas Mixture CS Mixes
Recommended Use: For general analytical/synthetic chemical gas mixture.
Usage Restrictions:

Section 2: Hazards Identification



Danger

Hazard Classification:

Aspiration Hazard (Category 1)
Gases Under Pressure
Reproductive Toxicity (Category 2)
Specific target organ toxicity (Repeated Exposure) (Category 2)
Specific target organ toxicity (Single Exposure) (Category 3)

Hazard Statements:

Contains gas under pressure; may explode if heated
May be fatal if swallowed and enters airways
May cause damage to organs through prolonged or repeated exposure
May cause respiratory irritation;
Suspected of damaging fertility or the unborn child
Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention:
Do not breathe dust/fume/gas/mist/ vapors/spray..
[In case of inadequate ventilation] wear respiratory protection.
Do not handle until all safety precautions have been read and understood.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, eye protection and face protection.
Obtain special instructions before use.

Response:

Do NOT induce vomiting.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If swallowed: Rinse mouth. Do NOT induce vomiting.
Immediately call a poison center or doctor.
If exposed or concerned: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight.
Store locked up.

Disposal:

Dispose of contents and/or container in accordance with applicable regulations.

Section 3: Composition/Information on Ingredients

	CAS #	Concentration
Ethane	74-84-0	1
Methane	74-82-8	1
Butane	106-97-8	1
Hexane	110-54-3	1
n-Pentane	109-66-0	1
Propane	74-98-6	1
Nitrogen	7727-37-9	94

Chemical Substance	Chemical Family	Trade Names
--------------------	-----------------	-------------

	Chemical Substance	Chemical Family	Trade Names
Ethane	ETHANE	Hydrocarbons, Aliphatic, Saturated	BIMETHYL: ETHANE, COMPRESSED; METHYLMETHANE; DIMETHYL; ETHYL HYDRIDE; UN 1035; C2H6
Methane	METHANE, COMPRESSED GAS	Hydrocarbons, Aliphatic, Saturated	FIRE DAMP; MARSH GAS; METHYL HYDRIDE; NATURAL GAS; METHANE; UN 1971; R50; CH4
Butane	BUTANE	Hydrocarbons, Aliphatic, Saturated	N-BUTANE; LIQUIFIED PETROLEUM GAS; NORMAL BUTANE; BUTYL HYDRIDE; LPG; UN 1011; C4H10
Hexane	HEXANE	Hydrocarbons, Aliphatic, Saturated	N-HEXANE; 1-HEXANE; HEXYL HYDRIDE; 1-HEXANE; NORMAL HEXANE; SKELLYSOLVE B; UN 1208; CAPROYL HYDRIDE; C6H14
n-Pentane	N-PENTANE	Hydrocarbons, Aliphatic, Saturated	PENTANE; AMYL HYDRIDE; UN 1265; C5H12
Propane	PROPANE	Hydrocarbons, Aliphatic, Saturated	N-PROPANE; DIMETHYLMETHANE; PROPYL HYDRIDE; R-290; PROPYLHYDRIDE; LIQUEFIED PETROLEUM GAS; LPG; >96% NATURAL GRADE; >99.9% PURE GRADE; UN 1978; C3H8
Nitrogen	NITROGEN, COMPRESSED GAS	Inorganic gases	DIATOMIC NITROGEN; DINITROGEN; NITROGEN; NITROGEN-14; NITROGEN GAS; UN 1066; N2

Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Ethane	If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Methane	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Butane	If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Not likely route of exposure.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Hexane	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Aspiration hazard. DO NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get immediate medical attention. Give artificial respiration if not breathing.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Long-term exposure to n-hexane can cause damage to the peripheral nervous system.
n-Pentane	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Aspiration hazard. DO NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get immediate medical attention. Give artificial respiration if not breathing.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.	Not available
Propane	If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Nitrogen	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Ethane	Carbon dioxide, regular dry chemical Large fires: Flood with fine water spray.	Toxic gases	- Any self-contained breathing apparatus with a full facepiece. - Any self-contained breathing apparatus with a full facepiece.
Methane	Carbon dioxide, regular dry chemical Large fires: Use regular foam or flood with fine water spray.	Carbon monoxide, carbon dioxide, water	- Respiratory protection may be needed for frequent or heavy exposure. Any self-contained breathing apparatus with a full facepiece. - Respiratory protection may be needed for frequent or heavy exposure. Any self-contained breathing apparatus with a full facepiece.
Butane	Carbon dioxide, regular dry chemical Large fires: Flood with fine water spray.	Carbon monoxide, carbon dioxide, water and toxic and irritating fumes.	- Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. - Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.
Hexane	Regular dry chemical, carbon dioxide, water, regular foam Large fires: Use regular foam or flood with fine water spray.	Carbon monoxide, carbon dioxide and toxic and irritating fumes	- Any appropriate escape-type, self-contained breathing apparatus. - Protective material types: rubber
n-Pentane	Regular dry chemical, carbon dioxide, water, regular foam Large fires: Use regular foam or flood with fine water spray.	Carbon monoxide, carbon dioxide and toxic and irritating fumes	- Any self-contained breathing apparatus with a full facepiece. - Any self-contained breathing apparatus with a full facepiece.
Propane	Regular dry chemical, high expansion foam Large fires: Flood with fine water spray.	Carbon monoxide, carbon dioxide, water and toxic and irritating fumes	- Any self-contained breathing apparatus with a full facepiece. - Any self-contained breathing apparatus with a full facepiece.
Nitrogen	Non-flammable. Use suitable extinguishing media for surrounding fire. Cylinders may rupture or explode if exposed to heat.	Non-flammable	Respiratory protection may be needed for frequent or heavy exposure.

Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Ethane	Keep unnecessary people away, isolate hazard area and deny entry. Do not touch spilled material. Ventilate closed spaces before entering.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
Methane	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
Butane	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch spilled material.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
Hexane	Keep unnecessary people away, isolate hazard area and deny entry.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray.
n-Pentane	Keep unnecessary people away, isolate hazard area and deny entry.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
Propane	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch spilled material.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
Nitrogen	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	No significant effects from contamination expected.	Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
Ethane	Contact emergency personnel immediately.	Not available
Methane	Not available	Not available
Butane	Stop leak, evacuate area. Use protective equipment. Contact emergency personnel.	None
Hexane	Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. Remove sources of ignition	Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-9302 (USA) or (202)426-2675 (USA).
n-Pentane	Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal.	Not available

	Methods for Cleanup	Other Information
Propane	Contact emergency personnel	None
Nitrogen	N/A	N/A

Section 7: Handling and Storage

	Handling	Storage
Ethane	Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
Methane	Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
Butane	Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.110.
Hexane	Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier.
n-Pentane	Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier.
Propane	Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
Nitrogen	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Ethane	TLV-TWA: 100ppm (Aliphatic hydrocarbon gases: Alkane C1 - C4) (ACGIH)
Methane	METHANE, COMPRESSED GAS: ALIPHATIC HYDROCARBON GASES ALKANE (C1-C4): 1000 ppm ACGIH TWA METHANE: No occupational exposure limits established. ALIPHATIC HYDROCARBON GASES ALKANE (C1-C4): 1000 ppm ACGIH TWA
Butane	N-BUTANE: 800 ppm (1900 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 800 ppm (1900 mg/m3) NIOSH recommended TWA 10 hour(s) LIQUIFIED PETROLEUM GAS (LPG): 1000 ppm (1800 mg/m3) OSHA TWA 1000 ppm (1800 mg/m3) NIOSH recommended TWA 10 hour(s) ALIPHATIC HYDROCARBON GASES ALKANE (C1-C4): 1000 ppm ACGIH TWA
Hexane	N-HEXANE: 500 ppm (1800 mg/m3) OSHA TWA 50 ppm (180 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 50 ppm ACGIH TWA (skin) 50 ppm (180 mg/m3) NIOSH recommended TWA 10 hour(s)
n-Pentane	PENTANE: 1000 ppm (2950 mg/m3) OSHA TWA 600 ppm (1770 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 750 ppm (2210 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 600 ppm ACGIH TWA 120 ppm (350 mg/m3) NIOSH recommended TWA 10 hour(s) 610 ppm (1800 mg/m3) NIOSH recommended ceiling 15 minute(s)
Propane	PROPANE: 1000 ppm (1800 mg/m3) OSHA TWA 1000 ppm (1800 mg/m3) NIOSH recommended TWA 10 hour(s) LIQUIFIED PETROLEUM GAS (LPG): 1000 ppm (1800 mg/m3) OSHA TWA 1000 ppm (1800 mg/m3) NIOSH recommended TWA 10 hour(s) ALIPHATIC HYDROCARBON GASES ALKANE (C1-C4): 1000 ppm ACGIH TWA
Nitrogen	NITROGEN, COMPRESSED GAS: NITROGEN: ACGIH (simple asphyxiant)

Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
Ethane	For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.	Any self-contained breathing apparatus with a full facepiece.
Methane	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure. Any self-contained breathing apparatus with a full facepiece.
Butane	For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.	Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.
Hexane	Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any appropriate escape-type, self-contained breathing apparatus.
n-Pentane	Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any self-contained breathing apparatus with a full facepiece.
Propane	For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.	Any self-contained breathing apparatus with a full facepiece.
Nitrogen	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Ethane	Gas	Colorless	Colorless	N/A	Gas	Sweet odor	N/A
Methane	Gas	Colorless	Colorless	N/A	Gas	Odorless	Tasteless
Butane	Gas	Colorless	Colorless	N/A	Gas	Faint petroleum-like odor	N/A
Hexane	Liquid	Clear	Colorless	N/A	Liquid	Faint odor, gasoline odor	N/A
n-Pentane	Liquid	Clear	Colorless	N/A	Liquid	Gasoline odor	N/A
Propane	Gas	Clear	Colorless	N/A	Gas	Gasoline odor	N/A
Nitrogen	Gas	Clear	Colorless	N/A	Gas	Odorless	Tasteless

	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Ethane	-211 F (-135 C) (CC)	Not available	912.01 (log = 2.97) (estimated from water solubility)	882 F (472 C)	0.125	0.03
Methane	-369 F (-223 C)	Not available	724.44 (log = 2.87) (estimated from water solubility)	999 F (537 C)	15%	5%
Butane	-76 F (-60 C) (CC)	Not available	630.96 (log = 2.80) (estimated from water solubility)	549 F (287 C)	0.085	0.019
Hexane	-9.4 F (-23 C) (CC); -7 F (-21.7 C) (CC)	IB	139315.68 (log = 5.148) (estimated from water solubility)	437 F (225 C)	0.075	0.011
n-Pentane	<-40 F (<-40 C) (CC)	IA	Not available	500 F (260 C)	0.078	0.014
Propane	-157 F (-105 C)	Not available	Not available	842 F (450 C)	0.095	0.021
Nitrogen	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
Ethane	-128 F (-89 C)	-297 F (-183 C)	28842 mmHg @ 21 C	1.05 (Air =1)	Not applicable	4.7% @ 20 C	Not applicable	899 ppm	Not applicable for gas. Refrigerated liquefied ethane will evaporate rapidly at room temperature	0.00852 cP @ 0 C
Methane	-260 F (-162 C)	-297 F (-183 C)	760 mmHg @ -161 C	0.555 (Air=1)	Not applicable	3.5% @ 17 C	Not applicable	Not available	Not applicable	0.01118 cP @ 27 C
Butane	30 F (-1 C)	-216 F (-138 C)	1557 mmHg @ 20 C	2.1 (Air=1)	0.5788 @ 0 C	0.15	Not applicable	6.16 ppm	Not applicable for gas. Liquefied n-butane will evaporate rapidly at room temperature	Not available
Hexane	156 F (69 C)	-139 F (-95 C)	124 mmHg @ 20 C	3 (Air=1)	0.6603	0.014% @ 20 C	Neutral	64-244 ppm	8.9 (n-butyl acetate = 1)	0.32 cP @ 25 C
n-Pentane	96.93 F (36.07 C)	-201.5 F (-129.7 C)	400 mmHg @ 18.5 C	2.5 (Air=1)	0.626	0.0004	Not available	2.2-5000 ppm	28.6 (butyl acetate=1)	<32 SUS
Propane	-40 F (-40 C)	-310 F (-190 C)	6398 mmHg @ 21.1 C	1.55 (Air=1)	0.5853 @ -45 C	Very slightly soluble	Not applicable	5000-20000 ppm	Not applicable	Not available
Nitrogen	-321 F (-196 C)	-346 F (-210 C)	760 mmHg @ -196 C	0.967 (Air=1)	Not applicable	1.6% @ 20 C	Not applicable	Not available	Not applicable	0.01787 cP @ 27 C

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
Ethane	30.07	C-H3-C-H3	1.242 g/L @ 25 C	Not available	Not available	1	Soluble: Benzene, ethanol
Methane	16.04	C-H4	0.717 g/L @ 0 C	Not available	Not applicable	Not applicable	Soluble: Alcohol, ether, benzene, organic solvents
Butane	58.12	C-H3-(C-H2)2-C-H3	Not available	Not available	100%	Not applicable	Soluble: Alcohol, ether, chloroform
Hexane	86.18	C-H3-(C-H2)4-C-H3	Not available	Not available	Not available	675 g/l VOC (w/v)	Soluble: Alcohol, ether, chloroform, acetone, organic solvents
n-Pentane	72.15g/mol	C5-H12	Not available	Not available	Not available	Not available	Soluble: Alcohol, ether, acetone, benzene, chloroform
Propane	44.11	C-H3-C-H2-C-H3	0.116	Not available	Not available	Not applicable	Soluble: Absolute alcohol, ether, chloroform, benzene, turpentine
Nitrogen	28.0134	N2	1.2506 g/L	Not available	100%	1	Soluble: Liquid ammonia

Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
Ethane	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, halogens,
Methane	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Halogens, oxidizing materials, combustible materials

	Stability	Conditions to Avoid	Incompatible Materials
Butane	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, halogen compounds
Hexane	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, halogens, combustible materials, chlorine dioxide, fluorine, nitrogen dioxide, potassium chlorate, chlorine, chlorosulfuric acid
n-Pentane	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, combustible materials, halogen compounds
Propane	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, combustible materials, halogen compounds,
Nitrogen	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Metals, oxidizing materials

	Hazardous Decomposition Products	Possibility of Hazardous Reactions
Ethane	Oxides of carbon	Will not polymerize.
Methane	Oxides of carbon	Will not polymerize.
Butane	Oxides of carbon.	Will not polymerize.
Hexane	Oxides of carbon	Will not polymerize.
n-Pentane	Oxides of carbon	Will not polymerize.
Propane	Oxides of carbon	Will not polymerize.
Nitrogen	Oxides of nitrogen	Will not polymerize.

Section 11: Toxicology Information

Acute Effects			
	Oral LD50	Dermal LD50	Inhalation
Ethane	Not available	Not available	Irritation, nausea, vomiting, irregular heartbeat, headache, dizziness, disorientation, emotional disturbances, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma
Methane	Not available	Not available	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, drowsiness, fatigue, dizziness, disorientation, mood swings, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma
Butane	LC(50): 658 mg/l (270,000 ppm) butane (4 hour-rat)	Not established	Irritation, nausea, vomiting, headache, drowsiness, symptoms of drunkenness, tingling sensation, suffocation, convulsions, coma, can displace oxygen at high concentrations
Hexane	>5 gm/kg oral-rat LD50	>2 gm/kg skin-rabbit LD50	Irritation, nausea, irregular heartbeat, headache, drowsiness, dizziness, mood swings, loss of coordination, lung congestion, nerve damage, brain damage, unconsciousness
n-Pentane	>2000 mg/kg oral-rat LD50	Not available	Irritation, nausea, difficulty breathing, headache, drowsiness, dizziness, disorientation, mood swings, loss of coordination, central nervous system depression, asphyxiant
Propane	LC50 Inhalation Gas, Rat >800000 ppm 15 minutes	Not available	Central nervous system depression, difficulty breathing, nausea, vomiting, irregular heartbeat, headache, symptoms of drunkenness, disorientation, suffocation, convulsions, coma
Nitrogen	Not available	Not available	Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions, coma

	Eye Irritation	Skin Irritation	Sensitization
Ethane	Frostbite	Frostbite	Difficulty breathing
Methane	No information on significant adverse effects	No information on significant adverse effects	Difficulty breathing
Butane	Frostbite, blurred vision	Blisters, frostbite	Central nervous system depression, difficulty breathing
Hexane	Mild irritation	Irritation	Reproductive toxicity, Category 2; H361f: Suspected of damaging fertility. Aspiration hazard, Category 1; H304: May be fatal if swallowed and enters airways. Specific Target Organ Toxicity (repeated exposure), Category 2; H373: May cause damage to organs through prolonged or repeated exposure. Skin irritation, Category 2; H315: Causes skin irritation. Specific Target Organ Toxicity (single exposure), Category 3; H336: May cause drowsiness or dizziness. Hazardous to the aquatic environment, Chronic Category 2; H411: Toxic to aquatic life with long lasting effects.
n-Pentane	Irritation	Irritation	Specific Target Organ Toxicity (single exposure), Category 3; H336: May cause drowsiness or dizziness. Aspiration hazard, Category 1; H304: May be fatal if swallowed and enters airways.
Propane	Liquid: frostbite, blurred vision	Liquid: blisters, frostbite	No health hazards classified.
Nitrogen	Contact with rapidly expanding gas may cause burns or frostbite	No information on significant adverse effects	Difficulty breathing

Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Ethane	Not Listed.	Not available	Not available	No data
Methane	Not available	Not available	Not available	No data
Butane	None	Not established	Not established	No data
Hexane	Not listed.	Available.	Available.	No data
n-Pentane	Not available	Not available	Not available	No data
Propane	Not available	Not available	Not available	No data
Nitrogen	Not hazardous	Not available	Not available	No data

Section 12: Ecological Information

Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Ethane	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available	Relatively non-persistent in the environment. Highly volatile from water.	Accumulates very little in the bodies of living organisms.	Leaches through the soil or the sediment at a slow rate.

	Other toxicity: Not available			
Methane	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Moderately volatile from water.	Accumulates very little in the bodies of living organisms.	Not expected to leach through the soil or the sediment.
Butane	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Expected to exist entirely in the vapor phase in ambient air	Not available	Not available	Not available
Hexane	Fish toxicity: 2500 ug/L 96 hour(s) LC50 (Mortality) Fathead minnow (Pimephales promelas) Invertebrate toxicity: Not available Algal toxicity: 75 ug/L 28 hour(s) (Population Growth) Green algae (Chlamydomonas sp) Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Highly volatile from water.	Accumulates very little in the bodies of living organisms.	Not expected to leach through the soil or the sediment.
n-Pentane	Fish toxicity: Not available Invertebrate toxicity: 3000000 ug/L 48 week(s) (Mortality) Pacific oyster (Crassostrea gigas) Algal toxicity: 1000 ug/L 8 year(s) EC50 (Photosynthesis) Algae, phytoplankton, algal mat (Algae) Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
Propane	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
Nitrogen	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

Section 13: Disposal Considerations

Disposal Considerations	
Ethane	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
Methane	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
Butane	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
Hexane	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
n-Pentane	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
Propane	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
Nitrogen	Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101
DOT Information For This Mixture

Shipping Name	Compressed gas, n.o.s. (Nitrogen, Propane)
UN Number	UN1956
Hazard Class	2.2
Hazard Information	Non-Flammable Gas

Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Ethane	Ethane	UN1035	2.1	Not applicable	2.1	Forbidden	150 kg	N/A
Methane	Methane, compressed	UN1971	2.1	Not applicable	2.1	Forbidden	150 kg	N/A
Butane	Butane	UN1011	2.1	Not applicable	2.1	Forbidden	150 kg	N/A
Hexane	Hexanes	UN1208	3	II	3	5 kg or L	N/A	N/A
n-Pentane	Pentanes	UN1265	3	II	3	N/A	N/A	N/A
Propane	Propane	UN1978	2.1	Not applicable	2.1	Forbidden	150 kg	N/A
Nitrogen	Nitrogen, compressed	UN1066	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A

Canadian Transportation of Dangerous Goods

	Shipping Name	UN Number	Class	Packing Group / Risk Group
Ethane	Ethane	UN1035	2.1	Not applicable
Methane	Methane, compressed	UN1971	2.1	Not applicable
Butane	Butane	UN1011	2.1	Not applicable
Hexane	Hexanes	UN1208	3	II
n-Pentane	Pentanes	UN1265	3	II
Propane	Propane	UN1978	2.1	Not applicable
Nitrogen	Nitrogen, compressed	UN1066	2.2	Not applicable

Section 15: Regulatory Information

U.S. Regulations

	CERCLA Sections	SARA 355.30	SARA 355.40
Ethane	Not regulated.	Not regulated.	Not regulated.
Methane	Not regulated.	Not regulated.	Not regulated.
Butane	Not regulated.	Not regulated.	Not regulated.
Hexane	5000 LBS RQ	Not regulated.	Not regulated.
n-Pentane	Not regulated.	Not regulated.	Not regulated.
Propane	Not regulated.	Not regulated.	Not regulated.
Nitrogen	Not regulated.	Not regulated.	Not regulated.

SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
Ethane	Yes	No	Yes	No	Yes
Methane	Yes	No	Yes	No	Yes
Butane	Yes	No	Yes	No	Yes
Hexane	Yes	Yes	Yes	No	No
n-Pentane	Yes	No	Yes	No	No
Propane	Yes	No	Yes	No	Yes
Nitrogen	Yes	No	No	No	Yes

SARA 372.65

Ethane	Not regulated.
Methane	Not regulated.
Butane	Not regulated.
Hexane	N-HEXANE
n-Pentane	Not regulated.
Propane	Not regulated.
Nitrogen	Not regulated.

OSHA Process Safety

Ethane	Not regulated.
Methane	Not regulated.
Butane	Not regulated.
Hexane	Not regulated.
n-Pentane	Not regulated.
Propane	Not regulated.
Nitrogen	Not regulated.

State Regulations

	CA Proposition 65
Ethane	Not regulated.
Methane	Not regulated.
Butane	Not regulated.
Hexane	WARNING: This product can expose you to chemicals including Hexane which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .
n-Pentane	Not regulated.
Propane	Not regulated.
Nitrogen	Not regulated.

Canadian Regulations

	WHMIS Classification
Ethane	A, B1.
Methane	A, B1
Butane	A,B1
Hexane	B2, D2A, D2B
n-Pentane	B2
Propane	A, B1.
Nitrogen	A

National Inventory Status

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Ethane	Listed on inventory.	Not listed.	Listed on inventory.
Methane	Listed on inventory.	Not listed.	Listed on inventory.
Butane	Listed on inventory.	Not listed.	Listed on inventory.
Hexane	Listed on inventory.	Not listed.	Listed on DSL
n-Pentane	Listed on inventory.	PENTANE CAS NUMBER: 109-66-0 SECTION 4	Listed on inventory.
Propane	Listed on inventory.	Not listed.	Listed on inventory.
Nitrogen	Listed on inventory.	Not listed.	Listed on inventory.

Section 16: Other Information

Other Information	
	NFPA Rating
Ethane	HEALTH=3 FIRE=4 REACTIVITY=0
Methane	HEALTH=0 FIRE=4 REACTIVITY=0
Butane	HEALTH=1 FIRE=4 REACTIVITY=0
Hexane	HEALTH=2 FIRE=3 REACTIVITY=0

n-Pentane	HEALTH=2 FIRE=4 REACTIVITY=0
Propane	HEALTH=2 FIRE=4 REACTIVITY=0
Nitrogen	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard